



Ordering Information

1288 HD Camera Control Unit
Part Number: 1288-010-000

1288 HD Camera Head and 20mm Coupler
Part Number: 1288-210-122

1288 HD Camera Head Only, C-Mount, 45°/ 10ft Cable
Part Number: 1288-210-105

1288 HD Inline Camera Head and 24mm Coupler, C-Mount, 0°/10ft Cable
Part Number: 1288-710-122

1288 HD Inline Camera Head Only, C-Mount, 0°/ 10ft Cable
Part Number: 1288-710-105

1288 HD Urology Camera Head with Integrated Coupler
Part Number: 1288-310-130

1288 HD 20mm Coupler, C-Mount
Part Number: 1288-020-122

1288 HD Camera 20ft Extension Cable
Part Number: 1288-000-020

L9000 LED Light source
Part Number: 220-210-000

stryker®

Joint Replacements

Trauma, Extremities & Deformities

Craniomaxillofacial

Spine

Biologics

Surgical Products

Neuro & ENT

Interventional Pain

Navigation

Endoscopy

Communications

Imaging

Patient Handling Equipment

EMS Equipment

Rehabilitation Services

www.stryker.co.kr

stryker®

Stryker Korea
서울시 강남구 삼성동 158-24
동성빌딩 11F
Tel : 02-565-7303
Fax : 02-565-3026
www.stryker.co.kr

The information presented in this brochure is intended to demonstrate a Stryker product. Always refer to the package insert, product label, and/or user instructions before using any Stryker product. Products may not be available in all markets. Product availability is subject to the regulatory or medical practices that govern individual markets. Please contact your Stryker representative if you have questions about the availability of Stryker products in your area.

stryker®

Endoscopy

The Revolutionary of HD Technology

Introducing Wireless 1080p

- 1288 HD 3-Chip* Camera
- L9000 LED Lightsource



The Revolution

of High Definition Technology

1288 HD 3-Chip® Camera

As the third generation in Stryker's HD 3-Chip® camera line, the 1288 HD 3-Chip® Camera features a 1920x1080p resolution along with nine specialty settings, resulting in optimum color resolution and brightness. Additional benefits of the 1288 HD 3-Chip® Camera include wireless transmission capabilities, four fully programmable buttons on the camera head, HD and HDTV outputs, and a touch screen LCD interface for easy navigation. By allowing for backwards compatibility with past generation digital capture devices, scopes and various flat panels, while also offering future capabilities with an optional fiber optic board, the 1288 HD 3-Chip® Camera continues to offer new solutions for improved visualization within the OR.



1288 HD 3-Chip® Camera Heads

High Definition Standardization



1288 HD 3-Chip® Regular Camera Head

- Ergonomic design for multi-specialty use
- Easy to rotate 20mm coupler design
- Fully programmable four buttons

1288 HD Urology 3-Chip® Camera Head

- 90° cable cable design for Urology, Gynecology & ENT procedures
- Rotating integrated 20mm coupler
- Built-in beam splitter provides direct eye viewing
- Ergonomic and light weight design



1288 HD Inline 3-Chip® Camera Head

- Optimum design for Endoscopic Vein Harvesting
- Easy to rotate 24mm coupler
- Right Angle Adapter for optimal work space



Unparalleled Resolution

And Clarity for the O.R.

Features:

- 1920 x 1080p resolution
- Enhanced clarity, depth of focus and sharpness
- L9000 light source control from the camera head
- Intuitive touch screen LCD interface



L9000 light source control from 1288 HD head by Firewire Connection

Light

Unlike Ever Before

L9000 LED Lightsource

Now an eco-friendly and cost-savings OR device, the L9000 LED Light Source reduces the environmental waste by eliminating the need to change the LED light bulb. The new design and Safelight™ technology within this light source provides a cooler light emission during procedures, making the device safer and more efficient for both the patients and OR staff. As an added benefit, the Safelight™ technology ensures that the light source goes into standby mode when the light cable detaches from the Safelight™. This will minimize injury to the patient and provide added protection in the OR.



Features:

- Intuitive simple user interface with LCD touch screen
- Control from the 1288 camera head
- Reduced lifetime ownership cost
- Increased patient and OR safety with Safelight™ cable



Safelight™ Fiberoptic Light Cables



Fully programmable buttons



20mm durable coupler with a single-hand focusing design



Ergonomic cable connector for reliable connection

O.R. Standardization

The 1288 HD Camera System continues to offer true standardization within the Operating Room

